

0.15~1.0\*305长压缩弹簧  
产品选型手册 • 2014



0.15~1.0长压缩弹簧（不锈钢/镀镍碳钢）

0.15 to 1.0 long compression spring (stainless steel / nickel-plated steel)



智翔弹簧

ZHIXIANG TANHUANG

# 压缩弹簧(长)

(公制)库存(长)压缩弹簧(0.15~1~长度305mm)

两端闭合不磨平, 不锈钢镀镍碳钢碳钢线去内应力处理。

表中所售弹簧价格为30个以内每个零售价, 30个以上请查看 [折扣表](#)

库存编号	线径		外径		工作杆径	工作孔径	长度		圈数	节距	压并高度	压并弹力	弹性系数		库存种类		
	MM	IN	MM	IN			MM	MM					MM	IN	N	MM	MM
P01500730S	0.15	0.00591	0.7	0.0276	0.35	0.8	305	12.008	873	0.35	131	0.608	1.04	106.5	◎	●	5.245
P01500830S	0.15	0.00591	0.8	0.0315	0.45	0.9	305	12.008	764	0.4	115	0.46	0.72	73.74	◎	●	5.247
P01500930S	0.15	0.00591	0.9	0.0354	0.55	1	305	12.008	679	0.45	102	0.36	0.53	54	◎	●	5.249
P01501030S	0.15	0.00591	1	0.0394	0.65	1.1	305	12.008	611	0.5	91.9	0.288	0.4	41.22	◎	●	5.25
P01501130S	0.15	0.00591	1.1	0.0433	0.75	1.2	305	12.008	556	0.55	83.6	0.236	0.32	32.48	◎	●	5.252
P01501230S	0.15	0.00591	1.2	0.0472	0.85	1.3	305	12.008	510	0.6	76.6	0.197	0.26	26.24	◎	●	5.254
P01501330S	0.15	0.00591	1.3	0.0512	0.95	1.4	305	12.008	471	0.65	70.8	0.166	0.21	21.64	◎	●	5.256
P01501430S	0.15	0.00591	1.4	0.0551	1.05	1.5	305	12.008	437	0.7	65.7	0.142	0.18	18.14	◎	●	5.257
P01501530S	0.15	0.00591	1.5	0.0591	1.15	1.6	305	12.008	408	0.75	61.4	0.123	0.15	15.43	◎	●	5.259
P01501730S	0.15	0.00591	1.7	0.0669	1.35	1.8	305	12.008	360	0.85	54.2	0.095	0.11	11.56	◎	●	5.262
P01502030S	0.15	0.00591	2	0.0787	1.65	2.1	305	12.008	307	1	46.2	0.068	0.08	7.996	◎	●	5.268
P02001230S	0.2	0.00787	1.2	0.0472	0.75	1.3	305	12.008	510	0.6	102	0.639	0.94	96	◎	●	5.335
P02001430S	0.2	0.00787	1.4	0.0551	0.95	1.5	305	12.008	437	0.7	87.6	0.463	0.64	64.81	◎	●	5.339
P02001630S	0.2	0.00787	1.6	0.063	1.15	1.7	305	12.008	383	0.8	76.8	0.35	0.46	46.65	◎	●	5.342
P02001830S	0.2	0.00787	1.8	0.0709	1.35	1.9	305	12.008	340	0.9	68.3	0.273	0.34	35.16	◎	●	5.346
P02002030S	0.2	0.00787	2	0.0787	1.55	2.1	305	12.008	307	1	61.5	0.219	0.27	27.43	◎	●	5.349
P02501530S	0.25	0.00984	1.5	0.0591	0.95	1.6	305	12.008	408	0.75	102	0.999	1.47	150	◎	●	5.214
P02502030S	0.25	0.00984	2	0.0787	1.45	2.1	305	12.008	307	1	76.9	0.546	0.71	72.89	◎	●	5.222
P02502530S	0.25	0.00984	2.5	0.0984	1.95	2.6	305	12.008	246	1.25	61.7	0.343	0.42	42.87	◎	●	5.231
P02503030S	0.25	0.00984	3	0.1181	2.45	3.1	305	12.008	205	1.5	51.5	0.235	0.28	28.17	◎	●	5.239
编号	线径mm	线径in	外径mm	外径in	工作杆径	工作孔径	长度mm	长度in	圈数	节距	压并高度	压并弹力	弹性系数n	弹性系数gf	零售价		

备注:

1. "●"为常备库存
2. "◎"为非常备库存, 可以定做
3. 库存编号: 在编号后增加“T”表示琴钢丝; “S”表示304不锈钢; “D”-镀镍高碳钢线。其他材料可以定做
4. 弹簧未经过立定处理
5. 特殊弹簧均可以定做, 具体请您联系我公司业务员
6. 长压簧的弹力为取自弹簧中间10mm长度弹簧的弹力为参考, 客户截断不同长度弹力会改变, 具体可咨询公司客服。
7. 所有规格和价格都可能发生变动, 恕不另行通知。

## 压缩弹簧(长)

(公制)库存(长)压缩弹簧(长度305mm)

两端闭合不磨平, 琴钢线碳钢线喷油处理。

表中所售弹簧价格为30个以内每个零售价, 30个以上请查看 折扣表

库存编号	线径		外径		工作杆径	工作孔径	长度		圈数	节距	压并高度	压并弹力	弹性系数		库存种类		
	MM	IN	MM	IN			MM	IN					N	MM	MM	kgf/mm	N/in
P03002530T	0.3	0.01181	2.5	0.0984	1.85	2.6	305	12.008	246	1.25	74	0.722	0.93	95.09	●	3.041	◎
P03003030T	0.3	0.01181	3	0.1181	2.35	3.1	305	12.008	205	1.5	61.8	0.493	0.6	61.73	●	3.067	◎
P03004030T	0.3	0.01181	4	0.1575	3.35	4.1	305	12.008	154	2	46.6	0.272	0.31	31.98	●	3.111	◎
P04003030T	0.4	0.01575	3	0.1181	2.15	3.1	305	12.008	205	1.5	82.3	1.599	2.14	218.5	●	3.508	◎
P04003530T	0.4	0.01575	3.5	0.1378	2.65	3.6	305	12.008	176	1.75	70.7	1.158	1.47	150.4	●	3.549	◎
P04004030T	0.4	0.01575	4	0.1575	3.15	4.1	305	12.008	154	2	62	0.876	1.08	109.7	●	3.586	◎
P04005030T	0.4	0.01575	5	0.1969	4.15	5.1	305	12.008	124	2.5	49.9	0.551	0.64	65.75	●	3.652	◎
P05003030T	0.5	0.01969	3	0.1181	1.95	3.1	305	12.008	205	1.5	103	3.99	5.88	600	●	3.759	◎
P05004030T	0.5	0.01969	4	0.1575	2.95	4.1	305	12.008	154	2	77.5	2.182	2.86	291.5	●	3.157	◎
P05005030T	0.5	0.01969	5	0.1969	3.95	5.1	305	12.008	124	2.5	62.3	1.369	1.68	171.5	●	3.94	◎
P06003030T	0.6	0.02362	3	0.1181	1.75	3.1	305	12.008	205	1.5	123	8.41	13.8	1406	●	4.085	◎
P06003530T	0.6	0.02362	3.5	0.1378	2.25	3.6	305	12.008	176	1.75	106	6.093	9.11	929.9	●	4.15	◎
P06004030T	0.6	0.02362	4	0.1575	2.75	4.1	305	12.008	154	2	92.9	4.603	6.46	659.5	●	4.209	◎
P06005030T	0.6	0.02362	5	0.1969	3.75	5.1	305	12.008	124	2.5	74.7	2.883	3.73	380.4	●	4.313	◎
P07004030T	0.7	0.02756	4	0.1575	2.55	4.1	305	12.008	154	2	108	8.655	13.1	1336	●	4.492	◎
P07005030T	0.7	0.02756	5	0.1969	3.55	5.1	305	12.008	123	2.5	87.1	5.418	7.4	755	●	4.613	◎
P07006030T	0.7	0.02756	6	0.2362	4.55	6.1	305	12.008	103	3	72.9	3.698	4.74	483.8	●	4.719	◎
P07007030T	0.7	0.02756	7	0.2756	5.55	7.1	305	12.008	88.7	3.5	62.8	2.681	3.29	336.1	●	4.814	◎

编号	线径mm	线径in	外径mm	外径in	工作杆径	工作孔径	长度mm	长度in	圈数	节距	压并高度	压并弹力	弹性系数n	弹性系数gf	零售价
----	------	------	------	------	------	------	------	------	----	----	------	------	-------	--------	-----

备注:

- "●"为常备库存
- "◎"为非常备库存, 可以定做
- 库存编号: 在编号后增加"T"表示琴钢丝; "S"表示304不锈钢; "D"=镀锌高碳钢线。其他材料可以定做
- 弹簧未经过立定处理
- 特殊弹簧均可以定做, 具体请您联系我公司业务员
- 长压簧的弹力为取自弹簧中间10mm长度弹簧的弹力为参考, 客户截断不同长度弹力会改变, 具体可咨询公司客服。
- 所有规格和价格都可能发生变动, 恕不另行通知。

# 压缩弹簧(长)

(公制)库存(长)压缩弹簧(长度305mm)

两端闭合不磨平，琴钢线碳钢线喷油处理。

表中所售弹簧价格为30个以内每个零售价，30个以上请查看 [折扣表](#)

库存编号	线径		外径		工作杆径	工作孔径	长度		圈数	节距	压并高度	压并弹力	弹性系数		库存种类		
	MM	IN	MM	IN	MM	MM	MM	IN					N	MM	MM	kgf/mm	N/in
P08006030T	0.8	0.0315	6	0.2362	4.35	6.1	305	12.008	103	3	83.3	6.386	8.56	873.9	◎	4.914	●
P08007030T	0.8	0.0315	7	0.2756	5.35	7.1	305	12.008	88.7	3.5	71.7	4.624	5.89	601.5	◎	5.017	●
P08008030T	0.8	0.0315	8	0.315	6.35	8.1	305	12.008	77.9	4	63.1	3.5	4.3	439	◎	5.111	●
P08010030T	0.8	0.0315	10	0.3937	8.35	10.1	305	12.008	62.7	5	50.9	2.202	2.58	263	◎	5.278	●
P08012030T	0.8	0.0315	12	0.4724	10.4	12.1	305	12.008	52.6	6	42.9	1.511	1.71	174.9	◎	5.426	●
P10006030T	1	0.03937	6	0.2362	3.95	6.1	305	12.008	103	3	104	15.92	23.5	2400	◎	5.967	●
P10008030T	1	0.03937	8	0.315	5.95	8.1	305	12.008	77.8	4	78.8	8.708	11.4	1166	◎	6.274	●
P10010030T	1	0.03937	10	0.3937	7.95	10.1	305	12.008	62.6	5	63.6	5.464	6.72	685.9	◎	6.535	●
P10012030T	1	0.03937	12	0.4724	9.95	12.1	305	12.008	52.5	6	53.5	3.742	4.42	450.8	◎	6.767	●
P10014030T	1	0.03937	14	0.5512	12	14.1	305	12.008	45.3	7	46.3	2.72	3.12	318.6	◎	6.976	●
P10016030T	1	0.03937	16	0.6299	14	16.1	305	12.008	39.9	8	40.9	2.066	2.32	237	◎	7.169	●
编号	线径mm	线径in	外径mm	外径in	工作杆径	工作孔径	长度mm	长度in	圈数	节距	压并高度	压并弹力	弹性系数n	弹性系数gf	零售价		

备注:

1. "●"为常备库存
2. "◎"为非常备库存，可以定做
3. 库存编号：在编号后增加“T”表示琴钢丝；“S”表示304不锈钢；“D”-镀镍高碳钢线。其他材料可以定做
4. 弹簧未经过立定处理
5. 特殊弹簧均可以定做，具体请您联系我公司业务员
6. 长压簧的弹力为取自弹簧中间10mm长度弹簧的弹力为参考，客户截断不同长度弹力会改变，具体可咨询公司客服。
7. 所有规格和价格都可能发生变动，恕不另行通知。